



14 2 600 V - ROME CABLE



RED WIRE









Cert
Fiber
Build

APPLICATION
BE APPLIED TO THE
SPACE OF THE JOINT

WARNING: THIS
PRODUCT IS A
SPECIALTY ITEM
CLOSE TO THE

INSULATION ONLY
R-19
Fiberglas Building Insulation
Should be taken when working
with an open flame
The facing on the
should not be set
with an open flame



R. BARRI... FA
E HENTELAPE
G.

F

BPTC

APPLI...
AS



















GREEN GROUND	○ ○ ○
OPEN NEUTRAL	○ ○ ●
OPEN HOT	○ ○ ○
NOY/GRN REVERSE	● ○ ●
HOT/NEV REVERSE	● ○ ○
CORRECT	○ ○ ●





CertainTeed
Fiber Glass
Building Insulation

INSULATE ON TOP OR WITH
OVERLAPPING OF REVERSE
THIS PAPER SHOULD BE RE
CHIMNEYS, FLUES AND SIMI
INSULATION ON GET WEAT
IF THIS MATERIAL IS USED
SPECIAL CARE SHOULD BE
CLOSE TO THE WALLS AND



THIS MATERIAL IS APPLIED OVER EXISTING INSULATION OR BETWEEN WOOD FRAMING AND CHIMNEYS, FLUES AND SIMILAR HEAT SOURCES. THIS PADDING SHOULD BE REMOVED TO PREVENT OVERHEATING OF RECESSED LIGHT FIXTURES. DO NOT INSULATE ON TOP OR WITHIN 2" OF SUCH DEVICES.

THIS MATERIAL IS APPLIED OVER EXISTING INSULATION OR BETWEEN WOOD FRAMING AND CHIMNEYS, FLUES AND SIMILAR HEAT SOURCES. THIS PADDING SHOULD BE REMOVED TO PREVENT OVERHEATING OF RECESSED LIGHT FIXTURES. DO NOT INSULATE ON TOP OR WITHIN 2" OF SUCH DEVICES.

THIS MATERIAL IS APPLIED OVER EXISTING INSULATION OR BETWEEN WOOD FRAMING AND CHIMNEYS, FLUES AND SIMILAR HEAT SOURCES. THIS PADDING SHOULD BE REMOVED TO PREVENT OVERHEATING OF RECESSED LIGHT FIXTURES. DO NOT INSULATE ON TOP OR WITHIN 2" OF SUCH DEVICES.

THIS MATERIAL IS APPLIED OVER EXISTING INSULATION OR BETWEEN WOOD FRAMING AND CHIMNEYS, FLUES AND SIMILAR HEAT SOURCES. THIS PADDING SHOULD BE REMOVED TO PREVENT OVERHEATING OF RECESSED LIGHT FIXTURES. DO NOT INSULATE ON TOP OR WITHIN 2" OF SUCH DEVICES.



FiberGlas Building

CAUTION: THIS VAPOR
IS DANGEROUS TO THE HEALTH
OF THE DWELLING.
WATER RESISTANT
APPLY TO THE EXTERIOR
SURFACE OF THE DWELLING.
DO NOT USE FOR INTERIOR
APPLICATIONS.

FOR USE WITH ALL TYPES OF
WOODWORK AND TRIM
DO NOT USE FOR INTERIOR
APPLICATIONS.



